

Symbols & Numerics

- * (asterisk), optional attribute values, 317
- = (equal sign), mandatory attribute values, 317

3000 series concentrator VSAs, 389–391
 802.1x Switchport Authentication, ACS
 configuration, 138

A

AAA (authentication, authorization, and
 accounting), configuring method lists, 55–58

accountActions table, 278

accounting, 10

ACS reports, 293

RADIUS+, 294

TACACS+, 293

VoIP+, 294

example of, 12

RADIUS, 49

remote accounting, configuring, 201

TACACS+, 36

AV pairs, 37–41

types of, 10–11

acl= attribute, 318

ACLs (access control lists)

creating, 219

downloadable, 165–166, 169

configuring, 218–220

troubleshooting, 237–238

ACS (Access Control Server)

802.1x Switchport Authentication,

configuring, 138

accounting reports, 293

RADIUS+, 294

TACACS+, 293

VoIP+, 294

ActivCard Token Servers, configuring, 267

adding new AAA clients, 121, 208–209

adding users to database, 114–116

address assignment, 163–165

administrative policies, switch configuration,
 142–143

Admission Control menu, 102

advanced configurations, 138

CRYPTOCARD Token Servers, configuring,
 268–269

database backups, performing, 275–276

database group mappings, configuring, 271

device synchronization, 277–280

downloadable IP ACLs, 165–166, 169

EAP support, configuring, 138

external databases, configuring, 244–262

External User Database menu, 104

features, 75

for Windows Server Version 2.0, 66

for Windows Server Version 2.1, 67

for Windows Server Version 2.3, 67–68

for Windows Server Version 2.6, 68–69

for Windows Server Version 3.0, 69

for Windows Server Version 3.1, 69–71

for Windows Server Version 3.2, 71

Group Setup menu, 92

interface configuration, 111

TACACS+ settings, 112

Interface Configuration menu, 100–102

local AAA pools, configuring, 134–136

NARs

applying to user groups, 158–159

configuring, 155–157

matching conditions, 155

shared NARs, 159

Network Configuration menu, 95–97

obtaining, 76

Online Documentation menu, 107

PassGo Defender Token Servers,

configuring, 267–268

positioning on network

dialup access, 82

VPNs, 83–84

wireless deployment, 85

- proxy distribution
 - configuring, 194–199
 - creating table entries, 196
- RADIUS Token Servers, configuring, 263, 265
- reinstalling, 81
- remote logging
 - configuring, 308–311
 - disabling, 312
- reports, 283–285
 - Access Device attributes, logging, 287
 - Administrative, 298–300
 - Backup and Restore system reports, 301
 - Device Command Set attributes, logging, 289
 - ExtDB Info attributes, logging, 291
 - Failed Attempts, 295
 - Filter Information attributes, logging, 290
 - Network Device Group attributes, logging, 288
 - Passed Authentication, 297
 - Service Monitoring system reports, 306
 - System, 300–307
 - user-defined attributes, logging, 285–288
- Reports and Activity menu, 104–106
- RSA SecurID Token Servers, configuring, 270
- SafeWord Token Servers, configuring, 269–270
- server configuration, 108–110
- service log options, 313–314
- Shared Profile Components menu, 94
- shared secret keys, troubleshooting, 214
- switches, configuring, 140
- System Configuration menu, 97–99
- UCP module, 123
 - enabling SSL on web server, 128
 - installing, 128–132
 - preparing for installation, 124–127
- user accounts
 - adding to database, 119–120
 - authenticating, 120
- user callback, configuring, 133–134
- user groups
 - configuring, 147–150
 - max sessions option, 160
 - password aging rules, 161–162
 - time-of-day access settings, 152–153
 - usage quotas, 161
 - VoIP support, 150–151
- User Setup menu, 90–91
- VASCO Token Servers, configuring, 265–267
- version 3.2
 - installing, 77–78, 80–81
 - software requirements, 76–77
- Windows domain authentication
 - configuring, 132
 - password options, 132
- ActivCard Token Servers, ACS configuration, 267
- adding
 - AAA clients, 121
 - to ACS database, 208–209
 - devices to network device groups, 193
 - users to ACS database, 114–116
- adding user accounts to database, 119–120
- addr= attribute, 318
- addr-pool= attribute, 318
- Administration Audit system reports, 302
- administrative policies, ACS configuration, 142–143
- Administrative reports (ACS), 298–300
- Admission Control menu (ACS), 102
- advanced ACS configuration, 138
 - administrative policies, 142–143
 - EAP support, 138
 - switches, 140
- advanced group settings, enabling, 149
- anacl#n attribute, 320
- applying NARs to user groups, 158–159

- AR (Access Registrar), 342–343
 - configuring, 358–359
 - extension points, 345–347
 - EPS, 348–350
 - installing, 354–357
 - options, 343
 - Policy Engine, 344–345
 - Proxy AAA, 351
 - Solaris 8 installation requirements, 352–353
 - subdirectories, 357–358
- Ascend RADIUS attributes, 405–416
- assigning
 - AAA clients to NDGs, 194
 - IP addresses to ACS user groups, 163–165
- attributes
 - Access Device, ACS report logging, 287
 - acl=, 318
 - addr=, 318
 - addr-pool=, 318
 - anacl#n, 320
 - autocmd=, 319
 - callback-dialstring=, 319
 - callback-line=, 319
 - callback-rotary=, 319
 - cmd=, 319
 - cmd-arg=, 319
 - Device Command Set, ACS report logging, 289
 - dns-servers=, 319
 - ExtDB Info, ACS report logging, 291
 - Filter Information, ACS report logging, 290
 - gw-password=, 320
 - idletime=, 320
 - inacl=, 320
 - ip-addresses=, 320
 - link-compression=, 321
 - load-threshold=, 321
 - max-links=, 321
 - nas-password=, 321
 - Network Device Group, ACS report logging, 288
 - nocallback-verify, 321
 - noescape=, 321
 - nohangup=, 322
 - oldprompts=, 322
 - outacl#, 322
 - outacl=, 322
 - pooldef#n, 322
 - pool-timeout=, 322
 - ppp-vj-slot-compression=, 322
 - priv-lvl=, 323
 - protocol=, 323
 - route#n, 323
 - route=, 323
 - routing=, 323
 - rte-ftp-in#n, 323
 - sap#n, 324
 - sap-fltr-in#n, 324
 - sap-fltr-out#n, 324
 - services=, 324
 - source-ip=, 324
 - timeout=, 324
 - tunnel-id=, 325
 - user-defined, ACS report logging, 285–288
 - wins-servers=, 325
 - zonelist=, 325
- authentication. *See also* authentication servers
 - configuring on Cisco devices, 6
 - debugging, 59–60
 - example of, 7–8
 - LEAP Proxy RADIUS server, 261–262
 - local authentication, configuring on Cisco routers, 53–59
 - of ACS users, 120
 - RADIUS, 42
 - basic operation, 43–44
 - encryption, 44
 - Token Servers, ACS configuration, 263–265
 - TACACS+, 15
 - accounting, 36–41
 - authorization, 20, 22–36
 - communication between NAS and AAA client, 16–17
 - encryption, 18–19

- header fields, 17–18
- packet types, 19–20
- authentication servers
 - Cisco Secure ACS for Windows Server Version 2.0, 66
 - Cisco Secure ACS for Windows Server Version 2.1, 67
 - Cisco Secure ACS for Windows Server Version 2.3, 67–68
 - Cisco Secure ACS for Windows Server Version 2.6, 68–69
 - Cisco Secure ACS for Windows Server Version 3.0, 69
 - Cisco Secure ACS for Windows Server Version 3.1, 69–71
 - Cisco Secure ACS for Windows Server Version 3.2, 71
- authorization, 8
 - configuring, 8–9
 - example of, 9–10
 - RADIUS, nonproprietary AV pairs, 46–48
 - TACACS+, 20
 - AV pairs, 22–36
- autocmd= attribute, 319
- AV pairs, 10, 317
 - acl= attribute, 318
 - addr= attribute, 318
 - addr-pool= attribute, 318
 - anacl#n attribute, 320
 - Ascend RADIUS, 405–416
 - autocmd= attribute, 319
 - callback-dialstring= attribute, 319
 - callback-line= attribute, 319
 - callback-rotary= attribute, 319
 - cmd= attribute, 319
 - cmd-arg= attribute, 319
 - dns-servers= attribute, 319
 - examples, 330–335
 - gw-password= attribute, 320
 - idletime= attribute, 320
 - inacl= attribute, 320
 - ip-addresses= attribute, 320
 - link-compression= attribute, 321
 - load-threshold= attribute, 321
 - mandatory, 317
 - max-links= attribute, 321
 - nas-password= attribute, 321
 - nocallback-verify attribute, 321
 - noescape= attribute, 321
 - nohangup= attribute, 322
 - oldprompts= attribute, 322
 - optional, 317
 - outacl# attribute, 322
 - outacl= attribute, 322
 - pooldef#n attribute, 322
 - pool-timeout= attribute, 322
 - PPP connections, configuring, 325–330
 - ppp-vj-slot-compression= attribute, 322
 - priv-lvl= attribute, 323
 - protocol= attribute, 323
 - RADIUS, 46–48
 - route#n attribute, 323
 - route= attribute, 323
 - routing= attribute, 323
 - rte-ftp-in#n attribute, 323
 - sap#n attribute, 324
 - sap-fltr-in#n attribute, 324
 - sap-fltr-out#n attribute, 324
 - services= attribute, 324
 - source-ip= attribute, 324
 - TACACS+, 22–41
 - timeout= attribute, 324
 - tunnel-id= attribute, 325
 - wins-servers= attribute, 325
 - zonelist= attribute, 325

B-C

- backups
 - performing on ACS database, 275
 - versus replication, 273
- BBSM (Building Broadband Service Manager)
 - RADIUS VSA, 392

- callback, configuring, 133–134, 154
- callback-dialstring= attribute, 319
- callback-line= attribute, 319
- callback-rotary= attribute, 319
- canceling scheduled ACS database backups, 276
- challenges of service providers, 341–342
- Cisco 3000 VPN Concentrator, CSACS VSAs, 389–391
- Cisco 5000 VPN Concentrator VSAs, 392
- Cisco CNS Access Registrar. *See* AR
- Cisco devices
 - AAA support, 12–13
 - authentication, configuring, 6
 - Cisco IOS routers, configuring for AAA, 210–211
 - Cisco IOS switches, configuring for AAA, 212
 - PIX firewalls, 212
 - set-based, 212
 - Wireless APs, 213–214
- Cisco Secure ACS for Windows Server Version 2.0, 66
- Cisco Secure ACS for Windows Server Version 2.1, 67
- Cisco Secure ACS for Windows Server Version 2.3, 67–68
- Cisco Secure ACS for Windows Server Version 2.6, 68–69
- Cisco Secure ACS for Windows Server Version 3.0, 69
- Cisco Secure ACS for Windows Server Version 3.1, 69–71
- Cisco Secure ACS for Windows Server Version 3.2, 71
- Cisco Secure Solution Engine, 71–72
- clients (AAA), adding to ACS database, 121
- cmd= attribute, 319
- cmd-arg= attribute, 319
- command accounting, 11
- command authorization sets
 - configuring, 229–231
 - deleting, 232
 - editing, 233
 - group profiles, configuring, 234–236
 - testing, 237
 - troubleshooting, 239–240
 - user profiles, configuring, 236–237
- commands, debug, 59–60
- communication of TACACS+ between NAS and AAA client, 16–17
- configuring
 - ACS, 108–110
 - 802.1x Switchport Authentication, 138
 - ActivCard Token Servers, 267
 - address assignment, 163–165
 - administrative policies on switches, 142–143
 - CRYPTOCARD Token Servers, 268–269
 - database group mappings, 271
 - EAP support, 138
 - external databases, 244–261
 - local AAA pools, 134, 136
 - PassGo Defender Token Servers, 267–268
 - RADIUS Token Servers, 263–265
 - remote logging, 308–311
 - RSA SecurID Token Servers, 270
 - SafeWord Token Servers, 269–270
 - service logs, 313–314
 - switches, 140
 - TACACS+ settings, 112
 - unknown user policy, 272
 - user callback, 133–134
 - user groups, 147–153, 160–162
 - VASCO Token Servers, 265–267
 - Windows domain authentication, 132
 - AR, 358–359
 - authentication
 - method lists, 55–58
 - on Cisco devices, 6
 - authorization, 8–9
 - Cisco IOS routers, local authentication, 53–59
 - command authorization sets, 229
 - group profiles, 234–236
 - PIX firewall preparation, 230

- router preparation, 229
- shared profile components, 230–231
- user profiles, 236–237
- database replication
 - primary servers, 274
 - secondary servers, 275
- distributed networks, 205–208
- distributed systems, remote accounting, 201
- downloadable ACLs, 165, 169, 218–220
- external RADIUS databases, LEAP, 261–262
- NARs, 155–157, 221–224
 - applying to user groups, 158–159
 - non-IP-based, 225–226
 - shared NARs, 159
- network device groups, 191–194
- PPP
 - callback, 154
 - with AV pairs, 325–328
- proxy distribution tables, 194, 197–199
 - creating entries, 196
- user accounts
 - adding new clients, 121
 - adding users to database, 119–120
 - authentication, 120
 - user groups (ACS) with TACACS+, 169–183
- connection accounting, 11
- Continue records, 36
- creating
 - ACLs, 219
 - entries in Proxy Distribution Table, 196
- CRYPTOCARD Token Servers, ACS configuration, 268–269
- CSDBsync, 278

D

- database (ACS)
 - adding AAA clients, 208–209
 - adding users, 114, 116
 - group mappings, configuring, 271
 - replication, 272–273

- primary servers, configuring, 274
- secondary servers, configuring, 275
- versus backup, 273
- Database Replication system reports, 302
- debugging authentication, 59–60
- deleting
 - command authorization sets, 232
 - NARs, 227
- devices
 - Cisco IOS routers, AAA configuration, 210–211
 - Cisco IOS switches, AAA configuration, 212–214
 - network device searches, performing, 202–203
- dialup access for ACS, 82
- disabling ACS remote logging, 312
- distributed networks, configuring, 205–208
- distributed systems, 187
 - enabling, 187–191
 - remote accounting, configuring, 201
- dns-servers= attribute, 319
- documentation, importance of, 240
- downloadable ACLs
 - configuring, 218–220
 - troubleshooting, 237–238
- downloadable IP ACLs, 165–169

E

- EAP (Extensible Authentication Protocol),
 - ACS configuration, 138
- editing
 - command authorization sets, 233
 - NARs, 226–227
- enabling distributed systems, 187–191
- encryption
 - RADIUS, 44
 - TACACS+, 18–19
- EPS (Extension Point Scripting), 347
- examples, 348–350

- examples
 - of accounting, 12
 - authentication, 7–8
 - of authorization, 9–10
 - of AV pairs, 330, 332, 335
- EXEC accounting, 11
- extension points (AR), 345–347
 - EPS, 348–350
- external ACS databases
 - configuring, 244–245
 - ODBC, configuring, 255–261
 - unknown user policy, configuring, 272
 - Windows NT/2000, configuring, 247–255
- external RADIUS databases, configuring LEAP, 261–262
- External User Database menu (ACS), 104

F-G

- Failed Attempts Report (ACS), 295
- fault tolerance, database replication, 272
 - primary servers, configuring, 274
 - secondary servers, configuring, 275
 - versus backup, 273
- Generic LDAP external databases, ACS
 - configuration, 252–253, 255
- group level ACS configuration
 - max sessions option, 160
 - modifying user groups, 147–150
 - password aging rules, 161–162
 - time-of-day access settings, configuring, 152–153
 - usage quotas, 161
 - VoIP support, 150–151
- group level configuration (ACS)
 - configuring with TACACS+, 169–178
 - Shell Command Authorization Sets, 178–183
 - User Level command authorization, 183

- IP assignment, 163–165
 - NARs, applying, 158–159
 - shared NARs, 159
- group profiles, applying to command
 - authorization sets, 234–236
- Group Setup menu (ACS), 92
- gw-password= attribute, 320

H-I

- hot spots, 341
- idletime= attribute, 320
- IETF attribute value pairs, 392–403
- immediate replication, performing from primary
 - ACS server, 275
- inacl= attribute, 320
- installing
 - ACS version 3.2, 77–81
 - AR, 354–357
 - requirements for Solaris 8, 352–353
 - subdirectories, 357–358
 - UCP module, 128–132
- Interface Configuration menu (ACS), 100–102
- IP pools, ACS configuration, 136
- ip-addresses= attribute, 320
- IP-based NARs, 222

J-K-L

- Juniper RADIUS VSAs, 417
- LDAP external databases, ACS configuration, 252–255
- LEAP (Lightweight Extensible Authentication Protocol) Proxy RADIUS Server
 - authentication, 261–262
- link-compression= attribute, 321
- load-threshold= attribute, 321
- local AAA pools, ACS configuration, 134–136
- local authentication, 9
 - configuring on Cisco routers, 53–59

locating network devices, 202–203
logging attributes in ACS reports
 Access Device attributes, 287
 Device Command Set attributes, 289
 ExtDB Info attributes, 291
 Filter Information attributes, 290
 Network Device Group attributes, 288
 user-defined attributes, 285, 288

M

mandatory attribute values, 317
 acl=, 318
 addr=, 318
 addr-pool=, 318
 autocmd=, 319
 callback-dialstring=, 319
 callback-line=, 319
 callback-rotary=, 319
 cmd=, 319
 cmd-arg=, 319
 dns-servers=, 319
 gw-password=, 320
 idletime=, 320
 inac1=, 320
 ip-addresses=, 320
 link-compression=, 321
 load-threshold=, 321
 max-links=, 321
 nas-password=, 321
 nocallback-verify, 321
 noescape=, 321
 nohangup=, 322
 oldprompts=, 322
 outacl#, 322
 outacl=, 322
 pooldef#n, 322
 pool-timeout=, 322
 ppp-vj-slot-compression=, 322
 priv-lvl=, 323
 protocol=, 323
 route=, 323

 routing=, 323
 services=, 324
 source-ip=, 324
 timeout=, 324
 tunnel-id=, 325
 wins-servers=, 325
 zonelist=, 325
manual backups, performing on ACS database, 276
matching conditions (NARs), 155
max sessions option (ACS user groups), 160
max-links= attribute, 321
messages, TACACS+, 20
method lists
 configuring, 55–58
 TEST1, applying to vty, 57
methods of authentication, 7
Microsoft RADIUS VSAs, 404–405
minimum requirements, installing AR on Solaris 8, 352–353

N

NARs (Network Access Restrictions)
 applying to user groups, 158–159
 configuring, 155–157, 221–224
 editing, 226–227
 IP-based, configuring, 222
 matching conditions, 155
 non-IP-based, configuring, 222, 225–226
 removing, 227
 shared NARs, 159
 troubleshooting, 238
nas-password= attribute, 321
NDG, performing network device searches, 202–203
network accounting, 11
Network Configuration menu (ACS), 95–97
network device groups
 adding devices, 193
 assigning AAA clients, 194
 configuring, 191–194

- network device searches, 202–203
- nocallback-verify attribute, 321
- noescape= attribute, 321
- nohangup= attribute, 322
- non-IP-based NARs, 222
 - configuring, 225–226
- nonproprietary RADIUS AV pairs, 46–48
- Nortel RADIUS VSAs, 416
- Novell NDS external databases,
 - ACS configuration, 249–251

O-P

- obtaining ACS, 76
- ODBC external databases,
 - ACS configuration, 255–261
- oldprompts= attribute, 322
- Online Documentation menu (ACS), 107
- optional attribute values, 317
- outacl#= attribute, 322
- outacl= attribute, 322
- packets, TACACS+, 19–20
 - header fields, 17–18
- Passed Authentication Report (ACS), 297
- PassGo Defender Token Servers,
 - ACS configuration, 267–268
- password aging rules (ACS user groups), 161–162
- passwords, 123
 - UCP module, 123
 - installing, 128, 132
 - preparing for installation, 124–128
 - Windows domain options, 132
- performing
 - ACS database backups, 275–276
 - immediate replication from primary ACS server, 275
 - network device searches, 202–203
- permit and deny conditions (NARs), 156

- PIX firewalls, configuring for AAA, 212
- pooldef#n attribute, 322
- pool-timeout= attribute, 322
- positioning ACS on network
 - dialup access, 82
 - VPNs, 83–84
 - wireless deployment, 85
- PPP callback, configuring, 154
- PPP connections, configuring on ACS with AV pairs, 325–328
 - applying ACL to dial interface, 328–330
- ppp-vj-slot-compression= attribute, 322
- prefixes, stripping from Proxy Distribution Table entries, 195
- preparing
 - for ACS device synchronization, 279
 - UCP module for installation, 124–127
 - enabling SSL on web server, 128
- priv-lvl= attribute, 323
- protocol= attribute, 323
- Proxy AAA, 351
- proxy distribution
 - configuring, 197–199
 - creating entries in Proxy Distribution Table, 196
- Proxy Distribution Table, 188
 - configuring, 194

R

- RADIUS, 12, 42
 - accounting, 49
 - reports, 294
 - AR, 342–343
 - configuring, 358–359
 - extension points, 345–350
 - installing, 354–358
 - options, 343
 - Policy Engine, 344–345
 - Proxy AAA, 351
 - Solaris 8 installation requirements, 352–353

- Ascend RADIUS attributes, 405–416
 - authorization, nonproprietary AV pairs, 46–48
 - basic operation, 43–44
 - encryption, 44
 - IETF attribute value pairs, 392–403
 - LEAP, 261–262
 - Token Servers, ACS configuration, 263–265
 - VSAs
 - Cisco 3000 VPN Concentrator VSAs, 389–391
 - Cisco 5000 VPN Concentrator VSAs, 392
 - Juniper RADIUS VSAs, 417
 - Microsoft RADIUS VSAs, 404–405
 - Nortel RADIUS VSAs, 416
 - RDBMS synchronization, 280
 - system reports, 302
 - recovering ACS database configuration
 - from backup files, 277
 - reinstalling ACS, 81
 - remote accounting, configuring, 201
 - remote logging, ACS
 - configuring, 308–311
 - disabling, 312
 - removing
 - command authorization sets, 232
 - NARs, 227
 - replication, 272–273
 - primary servers, configuring, 274
 - secondary servers, configuring, 275
 - versus backup, 273
 - reports (ACS), 283, 285
 - Access Device attributes, logging, 287
 - accounting, 293–294
 - Administrative, 298–300
 - Device Command Set attributes, logging, 289
 - ExtDB Info attributes, logging, 291
 - Failed Attempts, 295
 - Filter Information attributes, logging, 290
 - Network Device Group attributes, logging, 288
 - Passed Authentication, 297
 - System, 300–307
 - user-defined attributes, logging, 285, 288
 - Reports and Activity menu (ACS), 104–106
 - REQUEST messages, TACACS+, 20
 - resource accounting, 11
 - RESPONSE messages (TACACS+), 20
 - RFCs (Requests For Comments), AAA-related, 5
 - route#n attribute, 323
 - route= attribute, 323
 - routers (Cisco IOS), configuring for AAA, 210–211
 - routing= attribute, 323
 - RSA SecurID Token Servers, ACS
 - configuration, 270
 - rte-fts-in#n attribute, 323
-
- ## S
-
- SafeWord Token Servers, ACS configuration, 269–270
 - sap#n attribute, 324
 - sap-fltr-in#n attribute, 324
 - sap-fltr-out#n attribute, 324
 - scheduled backups, performing on
 - ACS database, 276
 - secret keys, 121
 - servers, configuring network device groups, 193–194
 - service logs (ACS), configuring, 313–314
 - service providers
 - challenge of, 341–342
 - value added services, 342
 - services= attribute, 324
 - set-based switches, configuring for AAA, 212
 - shared NARs, 159
 - Shared Profile components
 - command authorization sets
 - configuring, 228–231, 234–237
 - deleting, 232
 - editing, 233

- testing, 237
- troubleshooting, 239–240
- downloadable ACLs
 - configuring, 218–220
 - troubleshooting, 237–238
- NARs
 - configuring, 221–226
 - editing, 226–227
 - removing, 227
 - troubleshooting, 238
- Shared Profile Components menu (ACS), 94
- shared secret keys, troubleshooting, 214
- Shell Command Authorization Sets, 178, 181–183
- shell command authorization sets, versus PIX command authorization sets, 229
- sniffers, 8
- software requirements for ACS version 3.2, 76–77
- source-ip= attribute, 324
- SP (service provider) business model, 341
- SSL (Secure Sockets Layer), enabling on web server, 128
- START packets (TACACS+), 19
- Start records, 36
- Stop records, 36
- stripping entries from Proxy Distribution Table, 195
- subdirectories, AR, 357–358
- suffixes, stripping from Proxy Distribution Table entries, 195
- support for AAA on Cisco devices, 12–13
- switches
 - AAA configuration, 212
 - ACS configuration, 140
 - administrative policies, ACS configuration, 142–143
 - PIX firewalls, AAA configuration, 212
 - set-based, 212
 - Wireless APs, AAA configuration, 213–214
- synchronizing ACS devices, 277–280
- system accounting, 11
- System Configuration menu (ACS), 97–99
- System Reports (ACS), 300–307

T

- TACACS+, 12–13, 15
 - accounting, 36
 - AV pairs, 37–41
 - reports, 293
 - ACS user group configuration, 169–178
 - Shell Command Authorization Sets, 178–183
 - User Level command authorization, 183
 - authorization, 20
 - AV pairs, 317
 - acl= attribute, 318
 - addr= attribute, 318
 - addr-pool= attribute, 318
 - anacl#n attribute, 320
 - autocmd= attribute, 319
 - callback-dialstring= attribute, 319
 - callback-line= attribute, 319
 - callback-rotary= attribute, 319
 - cmd= attribute, 319
 - cmd-arg= attribute, 319
 - configuring PPP connections on ACS, 325–330
 - dns-servers= attribute, 319
 - examples, 330, 332, 335
 - gw-password= attribute, 320
 - idletime= attribute, 320
 - inacl= attribute, 320
 - ip-addresses= attribute, 320
 - link-compression= attribute, 321
 - load-threshold= attribute, 321
 - mandatory, 317
 - max-links= attribute, 321
 - nas-password= attribute, 321
 - nocallback-verify attribute, 321
 - noescape= attribute, 321
 - nohangup= attribute, 322
 - oldprompts= attribute, 322
 - optional, 317
 - outacl# attribute, 322
 - outacl= attribute, 322
 - pooldef#n attribute, 322

- pool-timeout= attribute, 322
- ppp-vj-slot-compression= attribute, 322
- priv-lvl= attribute, 323
- protocol= attribute, 323
- route#n attribute, 323
- route= attribute, 323
- routing= attribute, 323
- rte-ftr-in#n attribute, 323
- sap#n attribute, 324
- sap-ftr-in#n attribute, 324
- sap-ftr-out#n attribute, 324
- services= attribute, 324
- source-ip= attribute, 324
- timeout= attribute, 324
- tunnel-id= attribute, 325
- wins-servers= attribute, 325
- zonelist= attribute, 325
- communication between NAS and AAA client, 16–17
- encryption, 18–19
- packet header fields, 17–18
- packet types, 19–20
- TEST1 method lists, applying to vty, 57
- testing command authorization, 237
- time-of-day access settings, ACS user group configuration, 152–153
- timeout= attribute, 324
- troubleshooting
 - command authorization sets, 239–240
 - downloadable ACLs, 237–238
 - NARs, 238
 - shared secret keys, 214
- tunnel-id= attribute, 325
- types of AAA accounting, 10–11

U

- UCP (User Changeable Password) module, 123
 - installing, 128–132
 - preparing for installation, 124–127
 - enabling SSL on web server, 128
- unknown user policy, configuring on ACS
 - external databases, 272
- usage quotas (ACS user groups), 161
- user accounts (ACS)
 - adding to database, 119–120
 - authenticating, 120
- user authorization, 8
- user callback, ACS configuration, 133–134
 - configuring with TACACS+, 169–178
- user groups (ACS), 147–150
 - advanced group settings, enabling, 149
 - applying NARs, 158–159
 - configuring with TACACS+
 - User Level command authorization, 183
 - Shell Command Authorization Sets, 178–183
 - IP assignment, 163–165
 - max sessions option, configuring, 160
 - password aging rules, configuring, 161–162
 - shared NARs, 159
 - time-of-day access settings, configuring, 152–153
 - usage quotas, configuring, 161
 - VoIP support, configuring, 150–151
- User Level command authorization, 183
- User Password Changes system reports, 304
- user profiles, applying to command authorization sets, 236–237
- User Setup menu (ACS), 90–91
- users, adding to ACS database, 114, 116

V

- value added services, 342
- VASCO Token Servers, ACS configuration, 265–267
- viewing ACS reports, 106
- virtual authentication, 6
- virtual Telnet, 7
- VoIP (voice over IP),
 - accounting reports, 294
 - ACS user group configuration, 150–151
- VSAs (vendor specific attributes)
 - 3000 series concentrator VSAs, 389–391
 - BBSM VSA, 392
 - Cisco VPN 3000 Concentrator, 389–391
 - Cisco VPN 5000 Concentrator, 392
 - IETF attribute value pairs, 392–401, 403
 - Juniper RADIUS VSAs, 417
 - Microsoft RADIUS VSAs, 404–405
 - Nortel RADIUS VSAs, 416

W-X-Y-Z

- Windows domain authentication,
 - ACS configuration, 132
- Windows NT/2000 external databases, ACS configuration, 247–248
- wins-servers= attribute, 325
- wireless APs, AAA configuration, 213–214
- wireless deployment of ACS, 85
- wireless hot spots, 341

- XTACACS, 15

- zonelist= attribute, 325