

**Network+ Practice Questions Exam Cram 2 (Exam N10-002)**

Copyright © 2004 by Que Publishing

International Standard Book Number: 078973110X

**Warning and Disclaimer**

Every effort has been made to make this book as complete and as accurate as possible, but no warranty or fitness is implied. The information provided is on an "as is" basis. The author and the publisher shall have neither liability nor responsibility to any person or entity with respect to any loss or damages arising from the information contained in this book or from the use of the CD or programs accompanying it.

When reviewing corrections, always check the print number of your book. Corrections are made to printed books with each subsequent printing. To determine the print number of your book, view the copyright page. The print number is the right-most number on the line below the "First Printing" line. For example, the following indicates that this is the 1<sup>st</sup> printing of this title and it was printed in May 2003.

*First Printing: May 2003*

06 05 04 03      4 3 2 1

## Second Printing Errata

Pg	Error	Correction
18	Question 3, choice B: B. interconnect only networks of the same access protocol	B. interconnect <b>network segments</b> using the same access protocol
20	Question 13, third sentence: The second is configured for COM 3, IRQ 15, and I/O of 03E8-03EF.	The second is configured for COM 3, IRQ <b>9</b> , and I/O of 03E8-03EF.
21	Question 21, choices A and D: A. Bridge D. MAU	A. <b>Gateway</b> D. <b>Bridge</b>
25	Objective 1.6, answer 3: D	<b>B</b>
35	Objective 1.6, answer 3: Answer: D. Bridges specifically interconnect LANs that don't use the same access protocols. Bridges aren't routinely used for either rerouting data around LANs or replacing multiple repeaters.	Answer: <b>B</b> . Bridges specifically interconnect <b>LAN segments</b> that use the same access protocols. Bridges aren't routinely used for either rerouting data around LANs or replacing multiple repeaters.
37	Answer 18: Answer: A. A bridge is primarily used to connect networks that use different network access protocols. For example, a bridge is used to connect users on an Ethernet LAN and users on a token ring LAN. Wireless access points that have an Ethernet port employ a bridge to connect the IEEE 802.11b users and the Ethernet users.	Answer: A. A <b>gateway</b> is used to connect networks that use different network access protocols. For example, a <b>gateway</b> is used to connect users on an Ethernet LAN and users on a token ring LAN. Wireless access points that have an Ethernet port employ a <b>gateway</b> to connect the IEEE 802.11b users and the Ethernet users.
111	Question 1, third sentence: The second uses IRQ 5 and I/O range of D700-D80A.	The second uses IRQ <b>10</b> and I/O range of D700-D80A.

This errata sheet is intended to provide updated technical information. Spelling and grammar misprints are updated during the reprint process, but are not listed on this errata sheet.